

Atlanta HR558 - Dimension Data (TR 70/80)

▼ Currently under development.

 Print

SER	Size	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim Width	Tread Width		Tread Depth		Weight	Max PSI	Max Load		UTQG
			mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS	
70	155/70R13	75T	550	21.7	169	6.7	4.5	4.0~5.0	109.0	4.3	8	6.6	5.89	36	387	853	400 A A
	165/70R13	79T	570	22.4	165	6.5	5.0	4.0~5.5	120.0	4.7	9	7.0	6.48	36	437	963	400 A A
	175/70R13	82T	581	22.9	179	7.0	5.0	4.5~6.0	127.0	5.0	9	7.2	6.95	36	475	1047	400 A A
	185/70R13	86T	599	23.6	185	7.3	5.5	4.5~6.0	132.0	5.2	10	7.6	7.41	36	530	1168	400 A A
	175/70R14	84T	608	23.9	175	6.9	5.0	4.5~6.0	127.0	5.0	9	7.2	7.73	36	500	1102	400 A A
	185/70R14	88T	625	24.6	185	7.3	5.5	4.5~6.0	132.0	5.2	10	7.6	8.46	36	560	1235	400 A A
	195/70R14	91T	637	25.1	195	7.7	6.0	5.0~6.5	138.0	5.4	10	7.7	9.08	36	615	1356	400 A A
	205/70R14	95T	652	25.7	205	8.1	6.0	5.0~7.0	145.0	5.7	10	7.7	9.54	36	690	1521	400 A A
	205/70R15	96T	669	26.3	209	8.2	6.0	5.0~7.0	147.2	5.8	10	8.2	9.88	36	690	1521	400 A A
215/70R15	98T	683	26.9	221	8.7	6.5	5.0~7.0	156.0	6.1	10	8.3	10.29	36	750	1653	400 A A	
80	155/80R12	77T	554	21.8	155	6.1	4.5	4.0~5.0	107.0	4.2	9	7.2	6.51	36	412	908	400 A A
	135/80R13	70T	550	21.7	140	5.6	3.5	3.5~4.5	94.0	3.7	9	6.8	5.44	36	335	739	400 A A
	145/80R13	75T	560	22.0	145	5.7	4.0	3.5~5.0	100.0	3.9	9	7.0	5.67	36	387	853	400 A A
	155/80R13	79T	579	22.8	155	6.1	4.5	4.0~5.0	107.0	4.2	9	7.2	6.33	36	437	963	400 A A
	165/80R13	83T	596	23.5	159	6.3	4.5	4.0~5.5	114.0	4.5	10	7.6	6.75	36	475	1047	400 A A
	175/80R14	88T	634	25.0	180	7.1	5.0	4.5~6.0	120.0	4.7	10	7.7	8.40	36	560	1235	400 A A
	185/80R14	91T	651	25.6	184	7.2	5.0	4.5~6.0	128.0	5.0	10	7.8	8.92	36	615	1356	400 A A

*These data can be changed by manufacturer without prior notice.