

MILANZA HZ-I - Dimension Data (VR 30/35/40/45/50/55)

▼ Currently under development.



SER	Size	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim Width	Tread Width		Tread Depth		Weight	Max PSI		Max Load		UTQG
			mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD	KGS	LBS	
30	▼255/30ZR 20	92W												50	630	1389	240A.A A	
	▼265/30ZR 19	93W												50	650	1433	240A.A A	
	▼275/30ZR 19	96W												50	710	1565	240A.A A	
	▼275/30ZR 20	97W												50	730	1609	240A.A A	
	▼285/30ZR 20	99W												50	775	1709	240A.A A	
35	▼215/35ZR 18	84W												50	500	1102	240A.A A	
	▼215/35ZR 19	85W												50	515	1135	240A.A A	
	▼225/35ZR 19	88W	639		229		8.0	7.5-9	185		8		11.4	50	560	1235	240A.A A	
	▼225/35ZR 20	90W												50	600	1323	240A.A A	
	▼235/35ZR 19	91W	646		240		8.5	8.0-9.5	228		8		11.8	50	615	1356	240A.A A	
	▼245/35ZR 19	93W												50	650	1433	240A.A A	
	▼245/35ZR 20	95W	676		250		8.5	8.0-9.5	205		8		13.4	50	690	1521	240A.A A	
	▼255/35ZR 18	94W												50	670	1477	240A.A A	
	▼255/35ZR 20	97W												50	730	1609	240A.A A	
	▼265/35ZR 18	97W												50	730	1609	240A.A A	
40	205/40ZR16	83W XL	568	22.4	214	8.4	7.5	7.0 - 8.0	186	7.3	9	7.1	9.3	50	487	1074	240A.A A	
	▼205/40R17	84W XL	594	23.4	214	8.4	7.5	7.0 - 8.0	186	7.3	9	7.1	9.4	50	500	1102	240A.A A	
	215/40ZR17	83W	602	23.7	220	8.7	7.5	7.0 - 8.5	190	7.5	9	7.1	9.4	44	487	1074	240A.A A	
	▼215/40ZR 18	85W												44	515	1135	240A.A A	
	▼225/40ZR 18	92W	644		244		8.0	7.5-9.0	209		8		12.1	50	630	1389	240A.A A	
	▼235/40ZR 17	90W	618	24.3	243	9.6	8.5	8.0 - 9.5	212	8.3	9	7.1	11.5	44	600	1325	240A.A A	
	▼235/40ZR 18	95W												50	690	1521	240A.A A	
	▼245/40ZR 17	92W												44	630	1389	240A.A A	
	▼245/40ZR 18	97W	653		248		8.5	8.0-9.5	214		8		12.7	50	730	1609	240A.A A	
	▼255/40ZR 17	94W	634	25.0	260	10.2	9.0	8.0 - 10.0	220	8.7	10	7.7	11.8	44	670	1477	240A.A A	
45	195/45R15	78V	556	21.9	200	7.9	6.5	6.0 - 7.5	176	6.9	9	7.1	8.8	36	425	937	240A.A	
	195/45R16	84V XL	581	22.9	200	7.9	6.5	6.0 - 7.5	176	6.9	9	7.1	10.0	36	450	992	240A.A	
	205/45ZR 16	83W	589	23.2	210	8.3	7.0	6.5 - 7.5	180	7.1	9	7.1	9.9	44	487	1073	240A.A A	
	205/45ZR 17	88W	615	24.2	208	8.2	7.0	6.5 - 7.5	180	7.1	10	7.9	9.6	50	560	1235	240A.A A	
	215/45ZR 17	87W	625	24.6	220	8.7	7.0	7.0 - 8.0	194	7.6	10	7.9	10.6	44	545	1201	240A.A A	
	225/45ZR 17	94W XL	633	24.9	230	9.1	7.5	7.0 - 8.5	200	7.9	10	7.9	11.2	44	615	1356	240A.A A	
	▼225/45ZR 18	95W												50	690	1521	240A.A A	
	235/45ZR 17	97W XL	643	25.3	240	9.4	8.0	7.5 - 9.0	210	8.3	10	7.7	13.0	44	670	1477	240A.A A	
	245/45ZR 17	95W	651	25.6	250	9.8	8.0	7.5 - 9.0	216	8.5	10	7.9	13.2	44	690	1521	240A.A A	
	▼245/45ZR 18	100W												50	800	1764	240A.A A	
50	195/50R15	82V	577	22.7	200	7.9	6.0	5.5 - 7.0	176	6.9	9	7.1	8.6	36	475	1047	260A.A	
	195/50R 16	84V	600	23.6	195	7.7	6.0	5.5 - 7.0	176	6.9	9	7.1	9.1	36	500	1102	260A.A	
	205/50R 15	86V	585	23.0	205	8.1	6.5	5.5 - 7.5	184	7.2	9	7.5	9.0	36	530	1168	260A.A	
	205/50ZR 16	87W	609	24.0	205	8.1	6.5	5.5 - 7.5	180	7.1	10	7.9	11.0	44	545	1201	260A.A A	
	▼205/50ZR 17	93W												50	650	1433	260A.A A	
	▼215/50ZR 17	91W												44	615	1356	260A.A A	
	225/50ZR 16	92W	630	24.8	225	8.9	7.0	6.0 - 8.0	206	8.1	10	7.9	11.5	44	630	1389	260A.A A	
	▼225/50ZR 17	98W												50	750	1653	260A.A A	
55	185/55R 14	80V	560	22.0	185	7.3	6.0	5.0 - 6.5	164	6.5	9	7.1	9.1	36	450	992	260A.A	
	185/55R 15	82V	585	23.0	185	7.3	6.0	5.0 - 6.5	164	6.5	9	7.1	8.9	36	475	1047	260A.A	
	195/55R 15	85V	595	23.4	195	7.7	6.0	5.5 - 7.0	164	6.5	10	7.9	9.7	36	515	1135	260A.A	
	▼205/55R 15	88V	652	25.7	205	8.1	6.5	5.5 - 7.5	174	6.9	9	7.1	9.0	36	560	1235	260A.A	
	205/55R 16	91W	632	24.9	205	8.1	6.5	5.5 - 7.5	180	7.1	9	7.1	9.7	44	615	1356	260A.A A	
	215/55R 16	93W	642	25.3	215	8.5	7.0	6.0 - 7.5	190	7.5	10	7.9	11.8	44	650	1433	260A.A A	
	▼215/55R 17	98W												50	750	1653	260A.A A	
	225/55R 16	95W	652	25.7	225	8.9	7.0	6.0 - 8.0	196	7.7	10	7.9	11.6	44	690	1521	260A.A A	
▼225/55R 17	101W												50	825	1819	260A.A A		

*These data can be changed by manufacturer without prior notice.