

**Vanteza VR-I - Dimension Data (NR/SR/PR 70/80)**

▼ Currently under development.

 Print

SER	Size	Ply Rating	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim Width	Tread Width		Tread Depth		Weight	Max PSI	Max Load	
				mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS
70	195/70R15C	8	104/102S	655	25.8	195	7.7	6.0	5.0 ~ 7.0	146	5.7	11	8.7	12.7	65	950/900	2094/1984
80	145R12C	8	86/84P	543	21.4	145	5.7	4.0	3.5 ~ 5.0	98	3.9	10	8.0	6.4	65	530/500	1168/1102
	155R12C	8	88/86P	553	21.8	155	6.1	4.5	4.0 ~ 5.0	112	4.4	10	8.0	7.1	65	560/530	1235/1168
	155R13C	8	90/88N	580	22.8	155	6.1	4.5	4.0 ~ 5.0	110	4.3	10	7.9	7.5	65	600/560	1323/1235
	165R13C	8	94/92N	596	23.5	165	6.5	4.5	4.0 ~ 5.0	124	4.9	10	7.9	8.5	65	670/630	1477/1389
	175R13C	8	97/95Q	614	24.2	175	6.9	5.0	4.5 ~ 6.0	126	5.0	10	7.9	9.5	65	730/690	1609/1521
	185R13C	8	100/98N	626	24.6	185	7.3	5.5	5.0 ~ 6.5	140	5.5	12	9.5	9.9	65	800/730	1764/1609
	175R14C	8	99/98N	639	25.2	175	6.9	5.0	4.5 ~ 6.0	126	5.0	10	7.9	11.3	65	825/780	1819/1720
	185R14C	8	102/100N	651	25.6	185	7.3	5.0	5.0 ~ 6.5	130	5.1	11	8.7	12.2	65	850/800	1874/1764
	195R14C	8	106/104N	671	26.4	195	7.7	5.5	4.5 ~ 6.5	144	5.7	11	8.7	10.0	65	950/900	2094/1984
	205R14C	8	109/107P	682	26.9	210	8.3	6.0	5.5 ~ 6.5	154	6.1	12	9.2	12.9	65	1030/975	2271/2149
215R14C	8	112/110N	701	27.6	215	8.5	6.0	5.0 ~ 7.0	160	6.3	19	14.8	14.8	65	1120/1060	2469/2337	

\*These data can be changed by manufacturer without prior notice.